



1 Total length
2 Class of accuracy
3 Conformance Européenne
4 Year of manufacturing

5 Code of notify body
6 Mark of manufacturer
7 Number of EC-type certificate
8 Tension strength

MID standard blade

Bi-color coating and two-side printing
1. Easy recognition with different color on different side.
2. Same system on both sides.

GEAR FRAME

Direction change switch

Speedy retracting gear

Remarkable label

Accuracy:
Demass long steel tapes are in conformity with the basic requirements under the "Measuring Instruments Directive 2014/32/EU of the European Parliament and of the Council on Measuring Instruments" as well as the special requirements under Annex MI-008 material measures for Class II accuracy.

| Class II | Accuracy |
|----------|-----------|
| Length | Tolerance |
| 10m | ± 2,3 mm |
| 20m | ± 4,3 mm |
| 30m | ± 6,3 mm |
| 40m | ± 8,3 mm |
| 50m | ± 10,3 mm |

Accuracy tolerance

0.15mm
0.25mm

SUPERBLADE
Applied with special extruding process, the high performance nylon can thoroughly cover the whole blade to provide it with super abrasion resistance and the anti-corrosion functions like rust-proof, anti-acid, anti-alkalescence as well, to prolong its life to the extreme.

www.demass.com



